

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 First edition: 19.03.2003 Last revision: 24.10.2023 Supersedes version of: 11.09.2023 Version: 16.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Name : Repaplast Colour Finish Better Care Black  
 Product number : 02.3100.5000

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
 Use of the substance or preparation : Professional paint with adhesion promoter to durably restore plastic parts to their original state after weathering or repair.

##### 1.2.2. Uses advised against

No information available

#### 1.3. Details of the supplier of the safety data sheet

PCS Innotec International NV  
 Schans 4  
 BE - 2480 Dessel  
 T.: +32 (0) 14 32 60 01  
 F.: +32 (0) 14 32 60 12  
 hse@innotec.eu

Distributor:  
 Innotec Supplies Ltd.  
 Unit 25 Glenmore Business Park,  
 Telford RD  
 UK - SP2 7GL Salisbury, Wiltshire  
 T.: +44 (0)1722411744  
 F.: +44 (0)1722411788  
 info@innotecworld.com

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):  
 BIG : +32 (0) 14 58 45 45

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) no 1272/2008 (CLP)

Aerosol 1 H222;H229  
 Eye Irrit. 2 H319  
 STOT SE 3 H336

Full text of hazard classes, H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Contains :

Acetone; n-Butyl acetate; Butan-1-ol; 2-Methoxy-1-methylethyl acetate

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
 H229 - Pressurised container: May burst if heated.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P280 - Wear protective clothing, protective gloves, face shield, eye protection. P337+P313 - If eye irritation persists: Get medical advice/attention. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.
Extra phrases	: Without adequate ventilation formation of explosive mixtures may be possible.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) no 1272/2008 (CLP)
Acetone	CAS number: 67-64-1 EINECS / ELINCS number: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Dimethyl ether	CAS number: 115-10-6 EINECS / ELINCS number: 204-065-8 REACH-no: 01-2119472128-37	20 – 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
n-Butyl acetate	CAS number: 123-86-4 EINECS / ELINCS number: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	12,5 – 20	Flam. Liq. 3, H226 STOT SE 3, H336
Propane	CAS number: 74-98-6 EINECS / ELINCS number: 200-827-9 REACH-no: 01-2119486944-21	5 – 10	Flam. Gas 1A, H220 Press. Gas
Butane (Contains < 0,1% butadiene (203-450-8))	CAS number: 106-97-8 EINECS / ELINCS number: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	5 – 10	Flam. Gas 1A, H220 Press. Gas
Isobutane (Contains < 0,1% butadiene (203-450-8))	CAS number: 75-28-5 EINECS / ELINCS number: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	5 – 10	Flam. Gas 1A, H220 Press. Gas
2-Methoxy-1-methylethyl acetate	CAS number: 108-65-6 EINECS / ELINCS number: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) no 1272/2008 (CLP)
Butan-1-ol	CAS number: 71-36-3 EINECS / ELINCS number: 200-751-6 REACH-no: 01-2119484630-38	< 2,5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336 STOT SE 3, H335
Nitrocellulose (nitrogen content < 12,6%)	CAS number: 9004-70-0 EINECS / ELINCS number: /	< 2,5	Expl. 1.1, H201
Titanium oxide substance with national workplace exposure limit(s) (AT, BE, BG, DK, EE, ES, FR, GB, GR, HR, IE, LT, LV, PL, PT, RO, SE, SK)	CAS number: 13463-67-7 EINECS / ELINCS number: 236-675-5 REACH-no: 01-2119489379-17	≤ 0,5	Carc. 2, H351

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General advice	: In all cases of doubt, or when symptoms persist, seek medical attention.
Inhalation	: If you feel unwell, seek medical advice. Remove person to fresh air and keep comfortable for breathing.
Skin contact	: No irritant effect.
Eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	: Drink plenty of water. Seek medical advice. Move to fresh air.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause drowsiness or dizziness.
Skin contact	: Repeated exposure may cause skin dryness or cracking.
Eyes contact	: Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Carbon dioxide. Dry powder. Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire	: Toxic gases.

#### 5.3. Advice for firefighters

Firefighting instructions	: Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing.
------------------	--------------------------------------

##### 6.1.1. For non-emergency personnel

Protective equipment	: Refer to protective measures listed in Sections 7 and 8.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. This product and its container must be disposed of in a safe way, and as per local legislation.

Other information : Provide adequate ventilation.

### 6.4. Reference to other sections

Stable in use and storage conditions as recommended in item 7. Concerning personal protective equipment to use, see section 8. Concerning disposal/elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. In use, may form flammable vapour-air mixture.

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Take precautionary measures against static discharge. Eliminate all ignition sources if safe to do so.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Do not expose to temperatures exceeding 50 °C. Protect from sunlight. Store in a well-ventilated place. Keep in fireproof place. Store in a dry place. Keep away from ignition sources. Smoking is forbidden.

Technical condition(s) : Store in a well-ventilated place. The floor of the depot should be impermeable and designed to form a water-tight basin.

Special rules on packaging : Store in a closed container. Store under dry conditions. Keep only in original container.

### 7.3. Specific end use(s)

No information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Acetone (67-64-1)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Acetone
IOEL TWA	1210 mg/m <sup>3</sup>
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Dimethyl ether (115-10-6)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Dimethylether
IOEL TWA	1920 mg/m <sup>3</sup>
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Dimethyl ether

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dimethyl ether (115-10-6)	
WEL TWA (OEL TWA) [1]	766 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	958 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-Butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm
Remark	(Ongoing)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Butane (106-97-8)	
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (OEL TWA) [1]	1450 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	750 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51), (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Butan-1-ol (71-36-3)	
United Kingdom - Occupational Exposure Limits	
Local name	Butan-1-ol
WEL STEL (OEL STEL)	154 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Titanium oxide (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m <sup>3</sup> respirable 10 mg/m <sup>3</sup> total inhalable

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium oxide (13463-67-7)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
2-Methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No information available

### 8.1.3. Air contaminants formed

No information available

### 8.1.4. DNEL and PNEC

No information available

### 8.1.5. Control banding

No information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Safety glasses. Gloves. In case of inadequate ventilation wear respiratory protection.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Wear security glasses which protect from splashes

#### 8.2.2.2. Skin protection

##### Skin protection:

Wear suitable protective clothing

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Hand protection:

Where hand contact with the product may occur, the use of gloves (approved according to the EN374 standard) made from the following materials may provide suitable chemical protection: Butyl rubber. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available. In this case a lower breakthrough time may be acceptable as long as appropriate glove maintenance and replacement regimes are rigorously followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Depending on model and material, glove thickness generally should be greater than 0,35 mm. Suitability and durability of a glove is dependent on usage (= frequency and duration of contact), chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour under TLV. Recommended: filter type AX/P2

### 8.2.2.4. Thermal hazards

No information available

### 8.2.3. Environmental exposure controls

No information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Appearance	: Aerosol.
Odour	: characteristic.
Odour threshold	: Not available
Melting point/melting range	: Not available
Freezing point	: Not available
Boiling point/range	: Not applicable, since the product is an aerosol.
Flammability	: Not available
Explosive limits	: 1,2 – 26,2 vol %
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable, since the product is an aerosol.
Auto-ignition temperature	: 240 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not determined
Solubility	: Practically not miscible. Water: not soluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water (Log Pow)	: <
Vapour pressure	: 4000 hPa
Vapour pressure at 20 °C	: Not available
Density	: Not available
Relative density (water = 1)	: 0,8 (20 °C)
Vapour density	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosion limits : 1,2 – 26,2 vol %

#### 9.2.2. Other safety characteristics

V.O.C. (V.O.S.) : 678 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. In use, may form flammable/explosive vapour-air mixture.

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No information available

### 10.4. Conditions to avoid

No information available

### 10.5. Incompatible materials

No information available

### 10.6. Hazardous decomposition products

No information available

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

#### Acetone (67-64-1)

LD50/oral/rat	5800 mg/kg
LD50/dermal/rabbit	20000 mg/kg
LC50/inhalation/4h/rat	39 mg/m <sup>3</sup>

#### Dimethyl ether (115-10-6)

LC50/inhalation/4h/rat	309 mg/m <sup>3</sup>
------------------------	-----------------------

#### n-Butyl acetate (123-86-4)

LD50/oral/rat	10800 mg/kg
LD50/dermal/rabbit	> 17600 mg/kg
LC50/inhalation/4h/rat	> 21 mg/m <sup>3</sup>

#### Butane (106-97-8)

LC50/inhalation/4h/rat	658000 mg/mg <sup>3</sup>
------------------------	---------------------------

#### Butan-1-ol (71-36-3)

LD50/oral/rat	2292 mg/kg
LD50/dermal/rabbit	3430 mg/kg
LC50/inhalation/4h/rat	17,76 mg/m <sup>3</sup>

#### Titanium oxide (13463-67-7)

LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit	> 10000 mg/kg
LC50/inhalation/4h/rat	3,43 mg/l
LC50 Inhalation - Rat (Dust/Mist)	> 6,82 mg/l/4h

#### 2-Methoxy-1-methylethyl acetate (108-65-6)

LD50/oral/rat	8530 mg/kg
LD50/dermal/rabbit	> 5000 mg/kg
LC50/inhalation/4h/rat	> 10000 mg/m <sup>3</sup>

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.



# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Acetone (67-64-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>n-Butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Butan-1-ol (71-36-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
<b>2-Methoxy-1-methylethyl acetate (108-65-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

<b>Repaplast Colour Finish Better Care Black</b>	
Viscosity, kinematic	Not determined

### 11.2. Information on other hazards

No information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>Acetone (67-64-1)</b>	
LC50/96h/fish	5540 mg/l (static)
LC50 - Other aquatic organisms [1]	2262 mg/l (48h, Daphnia Magna)
EC50/48h/daphnia magna	8800 mg/l
<b>Dimethyl ether (115-10-6)</b>	
LC50 - Fish [2]	4600 – 10000 mg/l 96h
EC50 96h - Algae [1]	155 mg/l
<b>n-Butyl acetate (123-86-4)</b>	
LC50/96h/fish	18 mg/l (Pimephales promelas)
LC50 - Other aquatic organisms [1]	205 mg/l (24h, Daphnia magna)
EC50/48h/daphnia magna	44 mg/l
EC50 - Other aquatic organisms [1]	320 mg/l (96h, Algae)
<b>Butan-1-ol (71-36-3)</b>	
LC50/96h/fish	1376 mg/l (Pimephales promelas)
EC50/48h/daphnia magna	1328 mg/l
EC50 - Other aquatic organisms [2]	8500 mg/l (72h, Algae)
<b>Titanium oxide (13463-67-7)</b>	
LC50/96h/fish	> 1000 mg/l
LC50 - Fish [2]	> 10000 mg/l
EC50/24h/daphnia magna	2 mg/l
EC50 - Other aquatic organisms [1]	> 10000 mg/l
EC50 - Other aquatic organisms [2]	61 mg/l
NOEC (chronic)	0,01 mg/l rat
NOEC chronic algae	56000 mg/l

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2-Methoxy-1-methylethyl acetate (108-65-6)

LC50/96h/fish	100 – 180 (oncorhynchus mykiss)
EC50 - Other aquatic organisms [2]	> 500 mg/l Daphnia magna

### 12.2. Persistence and degradability

No information available

### 12.3. Bioaccumulative potential

#### Repaplast Colour Finish Better Care Black

Partition coefficient n-octanol/water (Log Pow)	<
---	---

### 12.4. Mobility in soil

No information available

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Endocrine disrupting properties

No information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment. Do not discharge into drains or rivers

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste / unused products	: Avoid release to the environment. Should not be landfilled with household waste.
European List of Waste (LoW, EC 2150/2002)	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 04 - metallic packaging

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

### 14.1. UN number or ID number

UN-No. (ADR)	: UN 1950
UN-No. (IMDG)	: UN 1950
UN-No. (IATA)	: UN 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: AEROSOLS, flammable
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: Aerosols, flammable
Transport document description (ADR)	: UN 1950 AEROSOLS, flammable, 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2
Transport document description (IATA)	: UN 1950 Aerosols, flammable, 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 2.1
Danger labels (ADR)	: 2.1
:	:



#### IMDG

Transport hazard class(es) (IMDG)	: 2.1
Danger labels (IMDG)	: 2.1
:	:



# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### IATA

Transport hazard class(es) (IATA) : 2.1

Danger labels (IATA) : 2.1



### 14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Further information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E0

Transport category (ADR) : 2

Tunnel restriction code : D

#### Transport by sea

Limited quantities (IMDG) : 1 L

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

#### Air transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### VOC Directive (2004/42)

V.O.C. (V.O.S.) : 678 g/l

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

No information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Last revision	Modified	
	Supersedes	Modified	
1.2		Modified	

Abbreviations and acronyms:	
	ACGIH = American Conference of Governmental Industrial Hygienists
	ADR = Accord européen sur le transport des marchandises dangereuses par Route
	ATE = Acute Toxicity Estimate
	CAS = Chemical Abstracts Service
	CLP = Classification, labelling and packaging
	CSR = Chemical Safety Report
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No-Effect Level
	DPD = Dangerous Preparation Directive
	DSD = Dangerous Substance Directive
	EINECS/ELINCS = European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	HTP = Haitallisiksi tunnetut pitoisuudet
	IATA = International Air Transport Association
	ICAO = International Civil Aviation Organization
	IMDG = International Maritime Code for Dangerous Goods
	IOELV = Indicative Occupational Exposure Limit Value (EU)
	LC50 = Lethal concentration, 50 percent
	LD50 = Lethal dose, 50 percent
	MAK = Maximale Arbeitsplatzkonzentrationen
	LEL = Lower Explosion Limit
	MAL-kode = Måleteknisk Arbejdshygienisk Luftbehov
	N.O.S. = Not Otherwise Specified
	NDS = Najwyższe Dopuszczalne Stężenie
	NDSch = Najwyższe Dopuszczalne Stężenie Chwilowe
	OEL = Occupational Exposure Limits
	PBT = Persistent, bioaccumulative and toxic
	PNEC = Predicted No-Effect Concentration

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	RID = Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail).
	STEL = Short term exposure limit
	STOT RE = specific target organ toxicity repeated exposure
	STOT SE = specific target organ toxicity single exposure
	SVHC = Substance of Very High Concern
	TLV = Threshold Limit Value
	TRGS = Technischen Regeln für Gefahrstoffe
	TWA = time weighted average
	UEL = Upper Explosion Limit
	VLA-EC = valores límite ambientales para la exposición de corta duración
	VLA-ED = valores límite ambientales para la exposición diaria
	VLE = Valeur Limite d'exposition
	VME = Valeur Limite de Moyenne d'exposition
	VOC = Volatile Organic Compounds
	vPvB = very Persistent and very Bioaccumulative
	WGK = Wassergefährdungsklasse

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
Expl. 1.1	Explosives, Division 1.1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

# Repaplast Colour Finish Better Care Black

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Press. Gas	Gases under pressure
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Disclaimer with regard to REACH:

The information provided in this Safety Data Sheet is consistent with the information in the Chemical Safety Report, as far as this information was available at the time of compilation (see last revision date).

Disclaimer:

The information of this Safety Data Sheet is based on the present state of our knowledge and on current EC and national laws, as the users' working conditions are beyond our knowledge and control. The user is always responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this Safety Data Sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information provided relates only to the specific product designated and may not be valid for such product used in combination with any other product. The product must not be used for any purposes other than those specified without first obtaining written handling instructions.